

# ULTIMA

Point of Use Coolers

Bottleless water dispensers  
for your home or office



**D-16A  
and  
D-16B**



**D-14A  
and  
D-14B**

Type A: Cold & Hot Model

Type B: Cold & Cook Model

Certificates: UL & Energy Star

# Point of Use Coolers

These dependable point of use dispensers offer years of reliable service, eliminating heavy 40 lb. bottles of water. Can be used with Filtration, Reverse Osmosis or Ultraviolet Water Purification systems.

## **CABINET**

High glossy cabinet, Front and Top: ABS plastic, Side: High polymer polyester coated steel panel or Pre-coated metal. Superior resistance to UV light.

## **COLOR**

D-16 available in Black, White and Off-white; D-14 available only in Off-white.

## **FAUCETS**

Durable structure. Self closing type. Easy to operate. Child-safe hot water faucet. Cup push or Standard lever type available.

## **DRIP TRAY**

Concealed, liftout design, high impact, durable ABS.

## **FLOW CONTROL**

Leakage-preventive dual floats valve system, in case of malfunction of the primary valve, the secondary valve stops the water inflow to minimize the damage on the property.

## **COLD WATER TANK**

Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.

## **COLD WATER**

Temperature is controlled to 35.6°F-53.6°F

## **THERMOSTAT**

(2°C-12°C) by adjustable thermostat, easily accessible on the back.

## **REFRIGERATION UNIT**

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled by accurately calibrated capillary tube.

## **HOT WATER TANK**

Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fire proof insulation.

## **HOT WATER**

Water temperature is controlled to nearly 185°F

## **THERMOSTAT**

(85°C) automatically, ON/OFF switch easily accessible on the back.

## **ELECTRICAL**

220V-240V (±10%) 50/60Hz, 100V-127V (±10%) 50/60Hz provided with power cord. Units of other power supplies available upon special order.

**QUALITY** Our models covered by these specifications are manufactured to comply with the standards of overseas quality program.

## **WARRANTY**

One year on the sealed refrigeration system and most component parts.

## **PACKING**

Export standard carton packing.

## **REFRIGERATION TYPE**

R134a



*For the best quality water, use  
Ultima Reverse Osmosis Systems  
with your bottleless PoU cooler.*